

# SOUNDCAM ULTRA SENSOR

Product data



## Highlights

- Real-time results at 100 fps
- IP54 protection
- Audible and ultrasound range
- Streaming via Ethernet (TCP/IP)
- Analysis up to 100 kHz

## Applications

- Road/traffic monitoring
- EOL testing/quality assurance
- Condition monitoring
- Non destructive testing
- Partial discharge localization



# SOUNDCAM ULTRA SENSOR

The First Sound Camera Sensor for Integration



# What is SoundCam?

The SoundCam Ultra Sensor is an acoustic camera covering the audible and ultrasonic frequency ranges. It has a USB and an ethernet interface, which allow connection to a remote PC. The supplied PC software will show the location of acoustic events in real-time at up to 100fps, overlaid on the camera image.

One or more of these sensors can be combined into your own applications to form complex machine monitoring, leak detection, or animal or traffic monitoring networks, for example. Since the ultrasonic range is also included, electrical discharge or sparking can be monitored over vast networks.

The light weight, compact and waterproofed design makes it highly suitable for drone use. No other acoustic camera is so small and flexible, opening up infinite possibilities for new applications!



## Hardware

Physical Properties	Dimensions	15 x 15 x 7.5 cm (5.9 x 5.9 x 2.9 inch)
	Weight	1.9 kg (4.4 lb)
	Waterproof	IP54
	Housing	Aluminium
	Mounting	4 x M6
	Operating temp	-20°C to 50°C (-4°F to 122°F)
Interfaces	Storage temp	-30°C to 60°C (-22°F to 140°F)
	USB	data streaming and firmware updates
Sensors	Ethernet	LAN for data streaming
	Microphones	72 digital MEMS
	Frequency range	Up to 100 kHz
	Sample rate	200 kHz
Optical Camera	Sound pressure	Max. 120 dB
	Resolution	24 bit
	Type	Digital
	Resolution	320x240 (50fps) or 640x480 (16fps)
Output	Aperture angle	70° (FoV horizontal)
	Shutter	Global shutter
		Acoustic map video
Communication		Video
	Logical	TCP/IP
Power	Physical	Local sound
	Input	Audio spectrum
		Ethernet or USB-B
		9 - 19V with power adapter

## Software features

OS	Windows (for Laptop/PC)
HMI	Keyboard, mouse, headphones
Protection	Password (unauthorized access protection)
Online Performance	Up to 100 acoustic fps, up to 50 optical fps
	Acoustic pictures, optical pictures, FFT and spectrogram
	Listen to local sound (broadband or frequency filtered)
	Place marker while measuring
	Buffer recording, trigger recording (SPL or frequency)
Offline Features	Long term measurements (average and peak-hold)
	Time weighting: fast, slow, impulse
	View acoustic results frame by frame
Export	Save and reload
	Replay in real-time or slow motion
Intuitive Usability	Listen to local sound
	Screenshots, video, sound
	Distance settings
	Frequency filters (narrow band, 1/3-octave and octave)
	Dynamic filter and low cut-off
	3 scaling modes: off, auto, smart (crest factor)



Svensk representant:  
<https://www.faleco.se>

CAE Software und Systems GmbH  
 Tel.: +49 5241/21142-0 | Fax: +49 5241/21142-29  
 info@cae-systems.de | www.cae-systems.de

